

Safety Data Sheet

according to Regulation (EC) No 1907/2006

SHERAprint-tray clear 2.0

Revision date: 04.02.2025

Product code: SD400141

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

SHERAprint-tray clear 2.0

UFI: 0080-70Y1-1009-CH52

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Light curing resin for additive manufacturing of individual trays

1.3. Details of the supplier of the safety data sheet**Manufacturer**

Company name:	DeltaMed GmbH	
Street:	Raiffeisenstraße 8a	
Place:	61169 Friedberg (GER)	
Telephone:	+49 6031 7283-0	Telefax: +49 6031 7283-29
E-mail:	info@deltamed.de	
Contact person:	Research and Development	
	Department	
E-mail:	info@deltamed.de	
Internet:	www.deltamed.de	
Responsible Department:	F&E	
	Telefax +49 6031 7283-29	

Supplier

Company name:	SHERA Werkstoff-Technologie GmbH
Street:	Espohlstraße 53
Place:	49448 Lemförde
Telephone:	+ 49 (0) 5443 9933-0
E-mail:	info@shera.de
Internet:	www.shera.de

1.4. Emergency telephone number:Giftinformationszentrum Universitätsklinikum Mainz
Telefon +49 6131 19240**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No 1272/2008**Skin Irrit. 2; H315
Skin Sens. 1; H317
Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

2.2. Label elements**Regulation (EC) No 1272/2008****Hazard components for labelling**urethane dimethacrylate (UDMA)
trimethylolpropane formal acrylate (CTFA)
Tricyclodecan dimethanol diacrylate (TCDDMDA)
Ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate**Signal word:** Warning

Safety Data Sheet

according to Regulation (EC) No 1907/2006


SHERAprint-tray clear 2.0

Revision date: 04.02.2025

Product code: SD400141

Page 2 of 11

Pictograms:



Hazard statements

- H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

- P261 Avoid breathing dust/vapours/spray.
P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing/eye protection.
P302+P352 IF ON SKIN: Wash with plenty of water and soap.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P391 Collect spillage.
P501 Dispose of contents/container in accordance with local regulation.

Special labelling of certain mixtures

Restricted to professional users.

2.3. Other hazards

Polymerization with heat evolution may occur in the presence of radical forming substances (e.g. peroxides), reducing substances, and/or heavy metal ions.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture of acrylic resins and initiators.

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
72869-86-4	urethane dimethacrylate (UDMA)			< 70 %
	Skin Sens. 1B, Aquatic Chronic 2; H317 H411			
66492-51-1	trimethylolpropane formal acrylate (CTFA)			< 40 %
	Skin Irrit. 2, Skin Sens. 1B, Aquatic Chronic 2; H315 H317 H411			
42594-17-2	Tricyclodecan dimethanol diacrylate (TCDDMDA)			< 20 %
	Skin Sens. 1B, Aquatic Chronic 2; H317 H411			
84434-11-7	Ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate			< 3 %
	282-810-6			
	Skin Sens. 1B, Aquatic Chronic 2; H317 H411			
5187-23-5	5-ethyl-1,3-dioxane-5-methanol			1 - < 5 %
	Eye Irrit. 2; H319			

Full text of H and EUH statements: see section 16.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

SHERAprint-tray clear 2.0

Revision date: 04.02.2025

Product code: SD400141

Page 3 of 11

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
72869-86-4		urethane dimethacrylate (UDMA)	< 70 %
		inhalation: LC50 = >5 mg/l (dusts or mists); dermal: LD50 = >2000 mg/kg; oral: LD50 = >5000 mg/kg	
66492-51-1		trimethylolpropane formal acrylate (CTFA)	< 40 %
		dermal: LD50 = 2001 mg/kg; oral: LD50 = 2001 mg/kg	
42594-17-2		Tricyclodecan dimethanol diacrylate (TCDDMDA)	< 20 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 2000 mg/kg	
84434-11-7	282-810-6	Ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate	< 3 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg	
5187-23-5		5-ethyl-1,3-dioxane-5-methanol	1 - < 5 %
		oral: LD50 = > 2000 mg/kg	

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Get medical advice/attention if you feel unwell. Immediately remove any contaminated clothing, shoes or stockings.

After inhalation

Get medical advice/attention if you feel unwell. Provide fresh air.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Immediately remove any contaminated clothing, shoes or stockings. If skin irritation occurs: Get medical advice/attention.

After contact with eyes

After eye contact: Rinse immediately carefully and thoroughly with eye-bath or water. If eye irritation persists: Get medical advice/attention.

After ingestion

Do NOT induce vomiting. Medical treatment necessary.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam, Extinguishing powder, Carbon dioxide.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide Carbon dioxide Hazardous decomposition products

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

SHERAprint-tray clear 2.0

Revision date: 04.02.2025

Product code: SD400141

Page 4 of 11

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Other information

Larger quantities: Take up mechanically (by pumping). Smaller quantities and/or residues: Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Do not breathe gas/fumes/vapour/spray.
Provide fresh air.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Advice on general occupational hygiene

It is essential for pregnant women to avoid inhaling the product and not to let it come in contact with the skin. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Protect from the action of light. Keep only in the original container at a temperature between 4 -25 °C. Can polymerize with intense heat release.

Hints on joint storage

No special measures are necessary.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

DNEL/DMEL values

CAS No	Name of agent	Exposure route	Effect	Value
DNEL type				
72869-86-4	urethane dimethacrylate (UDMA)			
Worker DNEL, long-term		dermal	systemic	1,3 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	3,3 mg/m³

Safety Data Sheet

according to Regulation (EC) No 1907/2006

SHERAprint-tray clear 2.0

Revision date: 04.02.2025

Product code: SD400141

Page 5 of 11

PNEC values

CAS No	Name of agent	
Environmental compartment		Value
72869-86-4	urethane dimethacrylate (UDMA)	
Freshwater		0,01 mg/l
Marine water		0,001 mg/l
Freshwater sediment		4,56 mg/kg
Marine sediment		0,46 mg/kg
Micro-organisms in sewage treatment plants (STP)		3,61 mg/l
Soil		0,91 mg/kg

8.2. Exposure controls

Individual protection measures, such as personal protective equipment

Eye/face protection

Eye glasses with side protection

Hand protection

Gloves should be replaced regularly, especially after extended contact with the product. For each work-place a suitable glove type has to be selected.

Skin protection

Wear suitable protective clothing.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	pink
Odour:	No data available
Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	not determined
Flammability:	flammable liquids
Lower explosion limits:	not determined
Upper explosion limits:	not determined
Flash point:	> 150 °C
Auto-ignition temperature:	not determined
Decomposition temperature:	not determined
pH-Value:	not determined
Water solubility:	not determined
Solubility in other solvents	
not determined	
Partition coefficient n-octanol/water:	not determined
Vapour pressure:	not determined
Density (at 20 °C):	1,1 g/cm ³
Relative vapour density:	not determined
Particle characteristics:	not applicable

9.2. Other information

Information with regard to physical hazard classes

Self-ignition temperature

Solid:

not applicable

Gas:

not applicable

Safety Data Sheet

according to Regulation (EC) No 1907/2006

SHERAprint-tray clear 2.0

Revision date: 04.02.2025

Product code: SD400141

Page 6 of 11

Other safety characteristics

Evaporation rate:	not determined
Solid content:	not determined
Viscosity / dynamic:	500 - 1000 mPa·s

Further Information

Product has not been tested. The statement is derived from the properties of the components.

SECTION 10: Stability and reactivity**10.1. Reactivity**

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Polymerization with heat evolution may occur in the presence of radical forming substances (e.g. peroxides), reducing substances, and/or heavy metal ions.

10.4. Conditions to avoid

Protect from the action of light. Keep only in the original container at a temperature between 4 -25 °C. Can polymerize with intense heat release.

10.5. Incompatible materials

Oxidising agent, Reducing agent, Heavy metals, Acids, Alkali (lye).

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity**

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

Safety Data Sheet

according to Regulation (EC) No 1907/2006

SHERAprint-tray clear 2.0

Revision date: 04.02.2025

Product code: SD400141

Page 7 of 11

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
72869-86-4	urethane dimethacrylate (UDMA)				
	oral	LD50 >5000 mg/kg	Rat	OECD 401	
	dermal	LD50 >2000 mg/kg	Rat	OECD 402	
	inhalation (4 h) dust/mist	LC50 >5 mg/l			
66492-51-1	trimethylolpropane formal acrylate (CTFA)				
	oral	LD50 2001 mg/kg			
	dermal	LD50 2001 mg/kg			
42594-17-2	Tricyclodecan dimethanol diacrylate (TCDDMDA)				
	oral	LD50 > 2000 mg/kg	Rat	OECD 423	
	dermal	LD50 > 2000 mg/kg	Rat	OECD 402	
84434-11-7	Ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate				
	oral	LD50 > 5000 mg/kg	Rat		
	dermal	LD50 > 2000 mg/kg	Rat		
5187-23-5	5-ethyl-1,3-dioxane-5-methanol				
	oral	LD50 > 2000 mg/kg	Rat	OECD 401	

Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

May cause an allergic skin reaction. (urethane dimethacrylate (UDMA); trimethylolpropane formal acrylate (CTFA); Tricyclodecan dimethanol diacrylate (TCDDMDA); Ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate)

May cause sensitization by skin contact.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Further information

The product has not been tested. The statement is derived from the properties of the single components.

SECTION 12: Ecological information

Safety Data Sheet

according to Regulation (EC) No 1907/2006

SHERAprint-tray clear 2.0

Revision date: 04.02.2025

Product code: SD400141

Page 8 of 11

12.1. Toxicity

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
72869-86-4	urethane dimethacrylate (UDMA)					
	Acute fish toxicity	LC50 10,1 mg/l	96 h	Danio rerio (zebrafish)	OECD 203	
	Acute algae toxicity	ErC50 >0,68 mg/l	72 h	Desmodesmus subspicatus	OECD 201	
	Acute crustacea toxicity	EC50 >1,2 mg/l	48 h	Daphnia magna (Big water flea)		
66492-51-1	trimethylolpropane formal acrylate (CTFA)					
	Acute fish toxicity	LC50 4 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)		
	Acute algae toxicity	ErC50 34 mg/l	72 h		OECD 201	
	Acute crustacea toxicity	EC50 20 mg/l	48 h		OECD 202	
42594-17-2	Tricyclodecan dimethanol diacrylate (TCDDMDA)					
	Acute fish toxicity	LC50 1,65 mg/l	96 h	Danio rerio (zebrafish)	OECD 203	
	Acute algae toxicity	ErC50 1,6 mg/l	72 h	Pseudokirchneriella subcapitata	OECD 201	
	Acute crustacea toxicity	EC50 2,36 mg/l	48 h	Daphnia magna (Big water flea)	OECD 202	
84434-11-7	Ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate					
	Acute fish toxicity	LC50 1,89 mg/l	96 h	Danio rerio		
	Acute algae toxicity	ErC50 1,01 mg/l	72 h	Desmodesmus subspicatus		
	Acute crustacea toxicity	EC50 2,26 mg/l	48 h	Daphnia magna		
5187-23-5	5-ethyl-1,3-dioxane-5-methanol					
	Acute fish toxicity	LC50 >1000 mg/l	96 h	Danio rerio (zebrafish)		
	Acute algae toxicity	ErC50 >1000 mg/l	72 h			
	Acute crustacea toxicity	EC50 2466 mg/l	48 h	Daphnia magna (Big water flea)		

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
72869-86-4	urethane dimethacrylate (UDMA)			
	Biodegradation	22 %	28	OECD 301 F
42594-17-2	Tricyclodecan dimethanol diacrylate (TCDDMDA)			
	OECD 301 F	27 %	56	
	Not readily biodegradable (according to OECD criteria)			
5187-23-5	5-ethyl-1,3-dioxane-5-methanol			
		> 90%	28	
	Readily biodegradable (according to OECD criteria).			

Safety Data Sheet

according to Regulation (EC) No 1907/2006

SHERAprint-tray clear 2.0

Revision date: 04.02.2025

Product code: SD400141

Page 9 of 11

12.3. Bioaccumulative potential

The product has not been tested.

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

The product has not been tested.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Do not allow uncontrolled discharge of product into the environment. Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Small quantities can be polymerized by light and the cured solid material can be disposed of with the regular garbage. Larger quantities must be disposed of following the regulations of the local authorities. Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

070208 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of plastics, synthetic rubber and man-made fibres; other still bottoms and reaction residues; hazardous waste

List of Wastes Code - used product

070208 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of plastics, synthetic rubber and man-made fibres; other still bottoms and reaction residues; hazardous waste

List of Wastes Code - contaminated packaging

070208 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of plastics, synthetic rubber and man-made fibres; other still bottoms and reaction residues; hazardous waste

Contaminated packaging

This material and its container must be disposed of as hazardous waste. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information**Land transport (ADR/RID)****14.1. UN number or ID number:**

UN 3082

14.2. UN proper shipping name:ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(ACRYLIC RESIN)**14.3. Transport hazard class(es):**

9

14.4. Packing group:

III

Hazard label:

9

Classification code:

M6

Special Provisions:

274 335 375 601

Limited quantity:

5 L

Excepted quantity:

E1

Transport category:

3

Hazard No:

90

Tunnel restriction code:

E

Safety Data Sheet

according to Regulation (EC) No 1907/2006

SHERAprint-tray clear 2.0

Revision date: 04.02.2025

Product code: SD400141

Page 10 of 11

Other applicable information (land transport)

SV 375: These substances, when carried in single or combination packagings of a net quantity not exceeding 5 litres of liquids or a net mass not exceeding 5 kg of solids per single or combination packaging, are not subject to the other provisions of ADR, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 3082
14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ACRYLIC RESIN)
14.3. Transport hazard class(es): 9
14.4. Packing group: III
Hazard label: 9
Classification code: M6
Special Provisions: 274 335 375 601
Limited quantity: 5 L
Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number or ID number: UN 3082
14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ACRYLIC RESIN)
14.3. Transport hazard class(es): 9
14.4. Packing group: III
Hazard label: 9
Special Provisions: 274, 335, 969
Limited quantity: 5 L
Excepted quantity: E1
EmS: F-A, S-F

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 3082
14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ACRYLIC RESIN)
14.3. Transport hazard class(es): 9
14.4. Packing group: III
Hazard label: 9
Special Provisions: A97 A158 A197
Limited quantity Passenger: 30 kg G
Passenger LQ: Y964
Excepted quantity: E1
IATA-packing instructions - Passenger: 964
IATA-max. quantity - Passenger: 450 L
IATA-packing instructions - Cargo: 964
IATA-max. quantity - Cargo: 450 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes
Danger releasing substance: ACRYLIC RESIN

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

Safety Data Sheet

according to Regulation (EC) No 1907/2006

SHERAprint-tray clear 2.0

Revision date: 04.02.2025

Product code: SD400141

Page 11 of 11

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3

National regulatory information

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

Skin Irrit: Skin irritation

Eye Irrit: Eye irritation

Skin Sens: Skin sensitisation

Aquatic Chronic: Chronic aquatic hazard

ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Skin Irrit. 2; H315	Calculation method
Skin Sens. 1; H317	Calculation method
Aquatic Chronic 2; H411	Calculation method

Relevant H and EUH statements (number and full text)

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H411 Toxic to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)