

Revision: 21.08.2025

Printing date 21.08.2025

Version number 3 (replaces version 2)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: SHERAprint-model desert
- · Article number: SD400410
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against:

No further relevant information available.

- · Application of the substance / the mixture: 3D printing material
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

SHERA Werkstoff-Technologie GmbH

Espohlstraße 53 D-49448 Lemförde GERMANY

sdb@shera.de

+ 49 (0) 54 43 - 9933 - 0

- · Further information obtainable from: Department of product security.
- · 1.4 Emergency telephone number:

Giftinformationszentrum-Nord +49 (0) 551-19240

(Information in german or english)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008:

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.Skin Sens. 1 H317 May cause an allergic skin reaction.

Repr. 1B H360FD May damage fertility. May damage the unborn child. Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008:

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms:







GHS07 GHS08 GHS09

· Signal word: Danger

· Hazard-determining components of labelling:

Aliphatic diacrylates

Acrylated resin

diphenyl(2,4,6- trimethylbenzoyl)phosphine oxide

· Hazard statements:

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H360FD May damage fertility. May damage the unborn child.

H410 Very toxic to aquatic life with long lasting effects.

· Precautionary statements:

P261 Avoid breathing mist/vapours/spray. P273 Avoid release to the environment.

P280 Wear protective gloves / protective clothing.

P302+P352 IF ON SKIN: Wash with plenty of water.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

(Contd. on page 2)



Printing date 21.08.2025 Version number 3 (replaces version 2)

Trade name: SHERAprint-model desert

(Contd. of page 1)

Revision: 21.08.2025

P337+P313 If eye irritation persists: Get medical advice/attention.

P501 Dispose of contents / container in accordance with local / regional / national / international regulations.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment:
- PBT: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Acrylic/methacrylate resins with additives.

Dangerous components:		
	Aliphatic diacrylates Repr. 1B, H360D; Aquatic Chronic 1, H410; Skin Sens. 1B, H317	25-90%
	Acrylated resin Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1B, H317	5-40%
CAS: 444649-70-1 EC number: 814-233-8 Reg.nr.: 01-2120271347-53	Acrylate resin Aquatic Chronic 2, H411	5-40%
CAS: 75980-60-8 EINECS: 278-355-8 Index number: 015-203-00-X	diphenyl(2,4,6- trimethylbenzoyl)phosphine oxide Repr. 1B, H360Fd; Aquatic Chronic 2, H411; Skin Sens. 1B, H317	0.1-2.5%
CAS: 85203-81-2 EINECS: 286-272-3	zinc Repr. 1B, H360D; Eye Irrit. 2, H319; Aquatic Chronic 3, H412	0.1-<0.3%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

In case of skin irritation, seek medical treatment.

Remove dirty clothing and wash before using again.

Immediately wash with water and soap and rinse thoroughly.

- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Rinse out mouth and then drink plenty of water.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents:

CO₂, powder or water spray. Fight larger fire with alcohol resistant foam.

Use fire extinguishing methods suitable to surrounding conditions.

· 5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Carbon dioxide (CO₂).

(Contd. on page 3)



Printing date 21.08.2025

Version number 3 (replaces version 2)

Trade name: SHERAprint-model desert

(Contd. of page 2)

Revision: 21.08.2025

Carbon monoxide (CO).

Pyrolysis products, toxic.

- · 5.3 Advice for firefighters
- Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

· Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.

Use respiratory protective device against the effects of fumes / dust / aerosol.

Wear protective clothing.

Avoid contact with skin and eyes.

· 6.2 Environmental precautions

Inform respective authorities in case of seepage into water course or sewage system.

Dilute with plenty of water.

Do not allow to enter sewers / surface or ground water.

· 6.3 Methods and material for containment and cleaning up

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Devices with local extraction are to be used for open handling.

Ensure good ventilation / exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage
- \cdot Requirements to be met by storerooms and receptacles:

Store only in the original receptacle.

Keep container in a well-ventilated, cool and dry place.

Store only in the tightly closed original container at room temperature.

Keep away from light.

Might polymerize with high heat release.

Storage temperature between 4 and 28°C.

- · Information about storage in one common storage facility: Not required.
- $\cdot \mbox{ Further information about storage conditions:} \\$

Do not store in a protective gas environment, as oxygen (in the air) is required for stabilisation.

- · Storage class: No information available.
- · 7.3 Specific end use(s) No further relevant information available.

GB



Printing date 21.08.2025

Version number 3 (replaces version 2)

Trade name: SHERAprint-model desert

(Contd. of page 3)

Revision: 21.08.2025

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· DNELs:			
Aliphatic	diacrylates		
Dermal	DNEL Worker - Long Term - Systemic effects 84 mg/kg (worker)		
Inhalative	DNEL Worker - Long Term - Systemic effects 29.6 mg/m ₃ (worker)		
444649-70	0-1 Acrylate resin		
Dermal	DNEL Worker - Long Term - Systemic effects 0.93 mg/kg (workers)		
Inhalative	DNEL Worker - Long Term - Systemic effects 3.29 mg/m ₃ (workers)		
75980-60-	8 diphenyl(2,4,6- trimethylbenzoyl)phosphine oxide		
Dermal	DNEL Worker - Long Term - Systemic effects 0.233 mg/kg (workers)		
Inhalative	DNEL Worker - Long Term - Systemic effects 0.822 mg/m₃ (worker)		
PNECs:			
75980-60-	8 diphenyl(2,4,6- trimethylbenzoyl)phosphine oxide		
PNEC Aquatic Compartment 140 mg/l (seawater)			
	1,400 mg/l (Freshwater)		

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Ensure good ventilation / exhaustion at the workplace.

Pregnant women should strictly avoid inhalation or skin contact.

The usual precautionary measures are to be adhered to when handling chemicals.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product. Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

· Material of gloves:

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material:

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection Goggles recommended during refilling

(Contd. on page 5)



Printing date 21.08.2025 Version number 3 (replaces version 2) Revision: 21.08.2025

Trade name: SHERAprint-model desert

· Body protection: Protective work clothing.

(Contd. of page 4)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Colour: Beige

Odour: characteristicMelting point/freezing point: Undetermined.

· Boiling point or initial boiling point and boiling

range Undetermined.
• Flammability Not applicable.

Lower and upper explosion limit

· Lower: Not determined. · Upper: Not determined.

Upper: Not determined.
 Flash point: Not applicable.
 Decomposition temperature: Not determined.
 pH

· Viscosity:

Kinematic viscosity
 Dynamic at 20 °C:
 Not determined.
 500-1,000 mPas

Solubility

water: Insoluble.
 Partition coefficient n-octanol/water (log value)
 Vapour pressure: Insoluble.
 Not determined.

Vapour pressure:Density and/or relative density

Density:
Density:
Relative density
Not determined.
Vapour density
Not determined.
Not determined.

· 9.2 Other information

· Appearance:

· Form: Fluid

· Important information on protection of health and environment, and on safety.

• **Ignition temperature:** Product is not selfigniting.

• Explosive properties: Product does not present an explosion hazard.

Void.

Solvent content:

 \cdot VOC (EC): 0,00 % \cdot Solids content: 0.0 %

· Change in condition:

Evaporation rate Not determined.

· Information with regard to physical hazard classes

· Self-heating substances and mixtures

· Explosives Void. · Flammable gases Void. · Aerosols Void. · Oxidising gases Void. · Gases under pressure Void. · Flammable liquids Void. Flammable solids Void. · Self-reactive substances and mixtures Void. · Pyrophoric liquids Void. · Pyrophoric solids Void.

(Contd. on page 6)



Printing date 21.08.2025 Version number 3 (replaces version 2) Revision: 21.08.2025

Trade name: SHERAprint-model desert

(Contd. of page 5)

Substances and mixtures, which emit flammable gases in contact with water
 Oxidising liquids
 Oxidising solids
 Organic peroxides
 Corrosive to metals
 Desensitised explosives

SECTION 10: Stability and reactivity

- 10.1 Reactivity No data available.
- · 10.2 Chemical stability No decomposition if used according to specifications.
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions Reacts with acids, alkalis and oxidising agents.
- · 10.4 Conditions to avoid

The product hardens under the influence of visible and UV light. Therefore, keep them in closed containers at 4 ° C -28 ° C with complete exclusion of light.

10.5 Incompatible materials

Oxidizing agents.

Reducing agents.

Acids.

Alkalis (alkalis).

Metal.

· 10.6 Hazardous decomposition products

If the product is exposed to fire, it can release caustic acrylate vapours.

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

		Based on available data, the classification criteria are not met.
Aliphati	ic diac	rylates
Oral	LD50	>2,000 mg/kg (Rat)
Dermal	LD50	>2,000 mg/kg (Rabbit)
Acrylate	ed resi	n
Oral	LD50	>2,000 mg/kg (Rat)
Dermal	LD50	>2,000 mg/kg (Rabbit)
444649-	70-1 A	crylate resin
Oral	LD50	>5,000 mg/kg (Rat)
Dermal	LD50	>2,000 mg/kg (Rabbit)
75980-6	0-8 di	phenyl(2,4,6- trimethylbenzoyl)phosphine oxide
Oral	LD50	>5.000 mg/kg (Rat)

- · Primary irritant effect:
- Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.

(Contd. on page 7)



Version number 3 (replaces version 2) Printing date 21.08.2025

Trade name: SHERAprint-model desert

(Contd. of page 6)

Revision: 21.08.2025

- · Reproductive toxicity
- May damage fertility. May damage the unborn child.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxic	<u>ity</u>			
Aquatic toxicity:				
Aliphatic diacrylates				
EC50/48h	2.36 mg/l (Daphnia (Daphnia magna)) (OECD 202)			
EC50/72 h	1.6 mg/l (Algae) (OECD 201)			
LC50/72 h	1.65 mg/l (Fish) (OECD 203)			
Acrylated i	resin			
EC50/48h	>34 mg/l (Daphnia (Daphnia magna)) (OECD 202)			
EC50/72 h	51 mg/l (Algae) (OECD 201)			
LC50/96 h	7.9 mg/l (Fish) (OECD 203)			
444649-70	1 Acrylate resin			
EC50	8.3 mg/l (Algae) (OECD 201)			
	17 mg/l (Daphnia (Daphnia magna)) (OECD 202)			
LC50/96 h	1.3 mg/l (Fish) (OECD 203)			
75980-60-8	diphenyl(2,4,6- trimethylbenzoyl)phosphine oxide			
LC50/96 h	1.4 mg/l (Fish) (OECD 203)			
EC50/48 h	3.53 mg/l (Daphnia (Daphnia magna)) (OECD 202)			

- 12.2 Persistence and degradability No further relevant information available. • 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · **vPvB**: Not applicable.
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Remark: Harmful to fish.
- · Additional ecological information:
- General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water.

Do not allow product to reach ground water, water course or sewage system.

Harmful to aquatic organisms.

Danger to drinking water if even small quantities leak into the ground.

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods
- · Recommendation:

Smaller quantities could be cured with light and can be disposed of as household waste. Larger quantities shall be disposed of as special waste in accordance with local regulations.

(Contd. on page 8)



Printing date 21.08.2025 Version number 3 (replaces version 2) Revision: 21.08.2025

Trade name: SHERAprint-model desert

· Waste disposal key:

(Contd. of page 7)

The waste disposal code as prescribed in the EuropeanWaste Catalogue (EWC) depends on the waste producer and can thus vary for a product. The waste disposal code should thus be obtained separately from the waste producer in each case.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water, if necessary together with cleansing agents.

14.1 UN number or ID number ADR, IMDG, IATA	UN3082
14.2 UN proper shipping name ADR	3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE LIQUID, N.O.S. (Aliphatic Diacrylate, Acryliertes Harz)
IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE LIQUID, N.O.S. (Aliphatic diacrylates, Acrylated resin) MARINE POLLUTANT
IATA	ENVIRONMENTALLY HAZARDOUS SUBSTANCE LIQUID, N.O.S. (Aliphatic diacrylates, Acrylated resin)
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
Class Label	9 Miscellaneous dangerous substances and articles.9
14.4 Packing group ADR, IMDG, IATA	III
14.5 Environmental hazards:	
Marine pollutant:	Symbol (fish and tree)
Special marking (ADR): Special marking (IATA):	Symbol (fish and tree) Symbol (fish and tree)
14.6 Special precautions for user	Warning: Miscellaneous dangerous substances an articles.
Hazard identification number (Kemler code):	90
EMS Number:	F-A,S-F
Stowage Category	A
14.7 Maritime transport in bulk according to IM instruments	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ):	5L
Excepted quantities (ÉQ):	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
Transport category:	3
Tunnel restriction code:	(-)
Remarks:	SV 375: These substances, when carried in single of



Revision: 21.08.2025

Printing date 21.08.2025 Version number 3 (replaces version 2)

Trade name: SHERAprint-model desert

	(Contd. of page
	5 litres of liquids or a net mass not exceeding 5 kg of solids per single or combination packaging, are not subject to the other provisions of ADR, provided the packaging meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
· IMDG	
 Limited quantities (LQ): Excepted quantities (EQ): 	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· IATA	
· Remarks:	A 197: These substances are not subject to other provisions of these Regulations when carried in single of combination packagings with a net quantity per single of inner packaging not exceeding 5L for liquids and a net weight not exceeding 5kg for substances, provided the packagings meet the general requirements of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.
· UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOU SUBSTANCE, LIQUID, N.O.S. (ALIPHATI DIACRYLATE, ACRYLIERTES HARZ), 9, III
	51/10/11/2/12, /10/11/2/12/11/2/, 5, III

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act
- · Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

- · Directive 2012/18/EU
- \cdot Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category E2 Hazardous to the Aquatic Environment
- Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National regulations:
- · Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on the state of knowledge and experience pertaining on the date of issue. The information is not to be taken as a guarantee of product properties and do not constitute the basis for a contractual legal relationship. The details must not be changed or transferred to other products. Duplication in an unchanged state is permissible.

(Contd. on page 10)



Printing date 21.08.2025

Version number 3 (replaces version 2)

Trade name: SHERAprint-model desert

(Contd. of page 9)

Revision: 21.08.2025

· Relevant phrases

- Causes skin irritation. H315
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H360D May damage the unborn child.
- H360Fd May damage fertility. Suspected of damaging the unborn child.
- Very toxic to aquatic life with long lasting effects. H410
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.
- · Department issuing SDS: Department of product security.

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1: Skin sensitisation - Category 1

Skin Sens. 1B: Skin sensitisation - Category 1B

Repr. 1B: Reproductive toxicity – Category 1B Repr. 1B: Reproductive toxicity – Category 1B Repr. 1B: Reproductive toxicity – Category 1B

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard — Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard — Category 3

· * Data compared to the previous version altered.

GB